

```

[ 0.000000] Booting Linux on physical CPU 0x0
[ 0.000000] Linux version 4.19.75-v7+ (dom@buildbot) (gcc version 4.9.3 (crosstool-NG
crosstool-ng-1.22.0-88-g8460611)) #1270 SMP Tue Sep 24 18:45:11 BST 2019
[ 0.000000] CPU: ARMv7 Processor [410fd034] revision 4 (ARMv7), cr=10c5383d
[ 0.000000] CPU: div instructions available: patching division code
[ 0.000000] CPU: PIPT / VIPT nonaliasing data cache, VIPT aliasing instruction cache
[ 0.000000] OF: fdt: Machine model: Raspberry Pi 3 Model B Plus Rev 1.3
[ 0.000000] Memory policy: Data cache writealloc
[ 0.000000] cma: Reserved 8 MiB at 0x3ac00000
[ 0.000000] On node 0 totalpages: 242688
[ 0.000000] Normal zone: 2133 pages used for memmap
[ 0.000000] Normal zone: 0 pages reserved
[ 0.000000] Normal zone: 242688 pages, LIFO batch:63
[ 0.000000] random: get_random_bytes called from start_kernel+0xac/0x4b4 with crng_init=0
[ 0.000000] percpu: Embedded 17 pages/cpu s39488 r8192 d21952 u69632
[ 0.000000] pcpu-alloc: s39488 r8192 d21952 u69632 alloc=17*4096
[ 0.000000] pcpu-alloc: [0] 0 [0] 1 [0] 2 [0] 3
[ 0.000000] Built 1 zonelists, mobility grouping on. Total pages: 240555
[ 0.000000] Kernel command line: coherent_pool=1M 8250.nr_uarts=0
bcm2708_fb.fbwidth=1360 bcm2708_fb.fbheight=768 bcm2708_fb.fbswap=1
vc_mem.mem_base=0x3ec00000 vc_mem.mem_size=0x40000000 console=ttyS0,115200
console=tty1 root=PARTUUID=5e3da3da-02 rootfstype=ext4 elevator=deadline fsck.repair=yes
rootwait quiet splash plymouth.ignore-serial-consoles
[ 0.000000] Dentry cache hash table entries: 131072 (order: 7, 524288 bytes)
[ 0.000000] Inode-cache hash table entries: 65536 (order: 6, 262144 bytes)
[ 0.000000] Memory: 939088K/970752K available (8192K kernel code, 629K rwddata, 2176K
rodata, 1024K init, 821K bss, 23472K reserved, 8192K cma-reserved)
[ 0.000000] Virtual kernel memory layout:
    vector : 0xffff0000 - 0xffff1000 ( 4 kB)
    fixmap : 0xffc00000 - 0xffff0000 (3072 kB)
    vmalloc : 0xbb800000 - 0xff800000 (1088 MB)
    lowmem : 0x80000000 - 0xbb400000 ( 948 MB)
    modules : 0x7f000000 - 0x80000000 ( 16 MB)
    .text : 0x(ptrval) - 0x(ptrval) (9184 kB)
    .init : 0x(ptrval) - 0x(ptrval) (1024 kB)
    .data : 0x(ptrval) - 0x(ptrval) ( 630 kB)
    .bss : 0x(ptrval) - 0x(ptrval) ( 822 kB)
[ 0.000000] SLUB: HWalign=64, Order=0-3, MinObjects=0, CPUs=4, Nodes=1
[ 0.000000] ftrace: allocating 26399 entries in 78 pages
[ 0.000000] rcu: Hierarchical RCU implementation.
[ 0.000000] NR_IRQS: 16, nr_irqs: 16, preallocated irqs: 16
[ 0.000000] arch_timer: cp15 timer(s) running at 19.20MHz (phys).
[ 0.000000] clocksource: arch_sys_counter: mask: 0xffffffffffffff max_cycles: 0x46d987e47,
max_idle_ns: 440795202767 ns
[ 0.000007] sched_clock: 56 bits at 19MHz, resolution 52ns, wraps every 4398046511078ns
[ 0.000018] Switching to timer-based delay loop, resolution 52ns
[ 0.000283] Console: colour dummy device 80x30
[ 0.000301] console [tty1] enabled
[ 0.000345] Calibrating delay loop (skipped), value calculated using timer frequency.. 38.40
BogoMIPS (lpj=192000)
[ 0.000361] pid_max: default: 32768 minimum: 301
[ 0.000702] Mount-cache hash table entries: 2048 (order: 1, 8192 bytes)

```

[0.000717] Mountpoint-cache hash table entries: 2048 (order: 1, 8192 bytes)
[0.001634] CPU: Testing write buffer coherency: ok
[0.002103] CPU0: thread -1, cpu 0, socket 0, mpidr 80000000
[0.002754] Setting up static identity map for 0x100000 - 0x10003c
[0.002902] rcu: Hierarchical SRCU implementation.
[0.003699] smp: Bringing up secondary CPUs ...
[0.004536] CPU1: thread -1, cpu 1, socket 0, mpidr 80000001
[0.005461] CPU2: thread -1, cpu 2, socket 0, mpidr 80000002
[0.006326] CPU3: thread -1, cpu 3, socket 0, mpidr 80000003
[0.006451] smp: Brought up 1 node, 4 CPUs
[0.006462] SMP: Total of 4 processors activated (153.60 BogomIPS).
[0.006468] CPU: All CPU(s) started in HYP mode.
[0.006473] CPU: Virtualization extensions available.
[0.007446] devtmpfs: initialized
[0.020730] VFP support v0.3: implementor 41 architecture 3 part 40 variant 3 rev 4
[0.020967] clocksource: jiffies: mask: 0xffffffff max_cycles: 0xffffffff, max_idle_ns:
19112604462750000 ns
[0.020986] futex hash table entries: 1024 (order: 4, 65536 bytes)
[0.021589] pinctrl core: initialized pinctrl subsystem
[0.022443] NET: Registered protocol family 16
[0.025460] DMA: preallocated 1024 KiB pool for atomic coherent allocations
[0.031171] hw-breakpoint: found 5 (+1 reserved) breakpoint and 4 watchpoint registers.
[0.031179] hw-breakpoint: maximum watchpoint size is 8 bytes.
[0.031386] Serial: AMBA PL011 UART driver
[0.033674] bcm2835-mbox 3f00b880.mailbox: mailbox enabled
[0.068353] bcm2835-dma 3f007000.dma: DMA legacy API manager at (ptrval), dmachans=0x1
[0.069991] SCSI subsystem initialized
[0.070269] usbcore: registered new interface driver usbfs
[0.070330] usbcore: registered new interface driver hub
[0.070425] usbcore: registered new device driver usb
[0.090129] raspberrypi-firmware soc:firmware: Attached to firmware from 2019-09-24 17:37,
variant start
[0.100384] raspberrypi-firmware soc:firmware: Firmware hash is
6820edeee4ef3891b95fc01cf02a7abd7ca52f17
[0.111794] clocksource: Switched to clocksource arch_sys_counter
[0.201304] VFS: Disk quotas dquot_6.6.0
[0.201387] VFS: Dquot-cache hash table entries: 1024 (order 0, 4096 bytes)
[0.201578] FS-Cache: Loaded
[0.201815] CacheFiles: Loaded
[0.211749] NET: Registered protocol family 2
[0.212552] tcp_listen_portaddr_hash hash table entries: 512 (order: 0, 6144 bytes)
[0.212589] TCP established hash table entries: 8192 (order: 3, 32768 bytes)
[0.212713] TCP bind hash table entries: 8192 (order: 4, 65536 bytes)
[0.212898] TCP: Hash tables configured (established 8192 bind 8192)
[0.213040] UDP hash table entries: 512 (order: 2, 16384 bytes)
[0.213087] UDP-Lite hash table entries: 512 (order: 2, 16384 bytes)
[0.213397] NET: Registered protocol family 1
[0.213974] RPC: Registered named UNIX socket transport module.
[0.213980] RPC: Registered udp transport module.
[0.213986] RPC: Registered tcp transport module.
[0.213991] RPC: Registered tcp NFSv4.1 backchannel transport module.
[0.215688] hw perfevents: enabled with armv7_cortex_a7 PMU driver, 7 counters available

```

[ 0.218676] Initialise system trusted keyrings
[ 0.218865] workingset: timestamp_bits=14 max_order=18 bucket_order=4
[ 0.228688] FS-Cache: Netfs 'nfs' registered for caching
[ 0.229260] NFS: Registering the id_resolver key type
[ 0.229286] Key type id_resolver registered
[ 0.229293] Key type id_legacy registered
[ 0.229309] nfs4filelayout_init: NFSv4 File Layout Driver Registering...
[ 0.231559] Key type asymmetric registered
[ 0.231568] Asymmetric key parser 'x509' registered
[ 0.231617] Block layer SCSI generic (bsg) driver version 0.4 loaded (major 250)
[ 0.231832] io scheduler noop registered
[ 0.231839] io scheduler deadline registered (default)
[ 0.232032] io scheduler cfq registered
[ 0.232040] io scheduler mq-deadline registered (default)
[ 0.232047] io scheduler kyber registered
[ 0.234235] bcm2708_fb soc:fb: FB found 1 display(s)
[ 0.264476] Console: switching to colour frame buffer device 170x48
[ 0.280916] bcm2708_fb soc:fb: Registered framebuffer for display 0, size 1360x768
[ 0.283063] bcm2835-rng 3f104000.rng: hwrng registered
[ 0.283366] vc-mem: phys_addr:0x00000000 mem_base=0x3ec00000
mem_size:0x40000000(1024 MiB)
[ 0.283901] vc-sm: Videocore shared memory driver
[ 0.284217] gpiomem-bcm2835 3f200000.gpiomem: Initialised: Registers at 0x3f200000
[ 0.295029] brd: module loaded
[ 0.305299] loop: module loaded
[ 0.305905] Loading iSCSI transport class v2.0-870.
[ 0.306622] libphy: Fixed MDIO Bus: probed
[ 0.306724] usbcore: registered new interface driver lan78xx
[ 0.306788] usbcore: registered new interface driver smsc95xx
[ 0.306804] dwc_otg: version 3.00a 10-AUG-2012 (platform bus)
[ 0.334655] dwc_otg 3f980000.usb: base=(ptrval)
[ 0.534900] Core Release: 2.80a
[ 0.534910] Setting default values for core params
[ 0.534943] Finished setting default values for core params
[ 0.735233] Using Buffer DMA mode
[ 0.735240] Periodic Transfer Interrupt Enhancement - disabled
[ 0.735246] Multiprocessor Interrupt Enhancement - disabled
[ 0.735253] OTG VER PARAM: 0, OTG VER FLAG: 0
[ 0.735272] Dedicated Tx FIFOs mode
[ 0.735740] WARN::dwc_otg_hcd_init:1045: FIQ DMA bounce buffers: virt = bad14000 dma =
0xfad14000 len=9024
[ 0.735766] FIQ FSM acceleration enabled for :
    Non-periodic Split Transactions
    Periodic Split Transactions
    High-Speed Isochronous Endpoints
    Interrupt/Control Split Transaction hack enabled
[ 0.735775] dwc_otg: Microframe scheduler enabled
[ 0.735834] WARN::hcd_init_fiq:457: FIQ on core 1
[ 0.735845] WARN::hcd_init_fiq:458: FIQ ASM at 80655664 length 36
[ 0.735858] WARN::hcd_init_fiq:497: MPHI regs_base at bb810000
[ 0.735875] dwc_otg 3f980000.usb: DWC OTG Controller
[ 0.735910] dwc_otg 3f980000.usb: new USB bus registered, assigned bus number 1

```

```
[ 0.735945] dwc_otg 3f980000.usb: irq 56, io mem 0x00000000
[ 0.735994] Init: Port Power? op_state=1
[ 0.736000] Init: Power Port (0)
[ 0.736255] usb usb1: New USB device found, idVendor=1d6b, idProduct=0002, bcdDevice=
4.19
[ 0.736266] usb usb1: New USB device strings: Mfr=3, Product=2, SerialNumber=1
[ 0.736276] usb usb1: Product: DWC OTG Controller
[ 0.736285] usb usb1: Manufacturer: Linux 4.19.75-v7+ dwc_otg_hcd
[ 0.736294] usb usb1: SerialNumber: 3f980000.usb
[ 0.736916] hub 1-0:1.0: USB hub found
[ 0.736960] hub 1-0:1.0: 1 port detected
[ 0.737544] dwc_otg: FIQ enabled
[ 0.737550] dwc_otg: NAK holdoff enabled
[ 0.737556] dwc_otg: FIQ split-transaction FSM enabled
[ 0.737566] Module dwc_common_port init
[ 0.737849] usbcore: registered new interface driver usb-storage
[ 0.738027] mousedev: PS/2 mouse device common for all mice
[ 0.738866] bcm2835-wdt bcm2835-wdt: Broadcom BCM2835 watchdog timer
[ 0.739107] bcm2835-cpufreq: min=600000 max=1400000
[ 0.739559] sdhci: Secure Digital Host Controller Interface driver
[ 0.739566] sdhci: Copyright(c) Pierre Ossman
[ 0.739936] mmc-bcm2835 3f300000.mmcnr: could not get clk, deferring probe
[ 0.740319] sdhost-bcm2835 3f202000.mmc: could not get clk, deferring probe
[ 0.740441] sdhci-pltfm: SDHCI platform and OF driver helper
[ 0.742037] ledtrig-cpu: registered to indicate activity on CPUs
[ 0.742190] hidraw: raw HID events driver (C) Jiri Kosina
[ 0.742396] usbcore: registered new interface driver usbhid
[ 0.742401] usbhid: USB HID core driver
[ 0.743192] vchiq: vchiq_init_state: slot_zero = (ptrval), is_master = 0
[ 0.744764] [vc_sm_connected_init]: start
[ 0.753983] [vc_sm_connected_init]: end - returning 0
[ 0.755092] Initializing XFRM netlink socket
[ 0.755118] NET: Registered protocol family 17
[ 0.755230] Key type dns_resolver registered
[ 0.755782] Registering SWP/SWPB emulation handler
[ 0.756417] registered taskstats version 1
[ 0.756434] Loading compiled-in X.509 certificates
[ 0.763738] uart-pl011 3f201000.serial: cts_event_workaround enabled
[ 0.763826] 3f201000.serial: ttyAMA0 at MMIO 0x3f201000 (irq = 81, base_baud = 0) is a
PL011 rev2
[ 0.765784] mmc-bcm2835 3f300000.mmcnr: mmc_debug:0 mmc_debug2:0
[ 0.765795] mmc-bcm2835 3f300000.mmcnr: DMA channel allocated
[ 0.791990] sdhost: log_buf @ (ptrval) (fad13000)
[ 0.829180] mmc1: queuing unknown CIS tuple 0x80 (2 bytes)
[ 0.840431] mmc0: sdhost-bcm2835 loaded - DMA enabled (>1)
[ 0.841749] of_cfs_init
[ 0.841969] of_cfs_init: OK
[ 0.842607] Waiting for root device PARTUUID=5e3da3da-02...
[ 0.870665] mmc1: queuing unknown CIS tuple 0x80 (67 bytes)
[ 0.872248] mmc1: queuing unknown CIS tuple 0x40 (0 bytes)
[ 0.876028] mmc1: queuing unknown CIS tuple 0x08 (0 bytes)
[ 0.878544] mmc1: queuing unknown CIS tuple 0x10 (0 bytes)
```

[0.880442] mmc1: queuing unknown CIS tuple 0x04 (0 bytes)
[0.882962] mmc1: queuing unknown CIS tuple 0x04 (0 bytes)
[0.886107] mmc1: queuing unknown CIS tuple 0x01 (0 bytes)
[0.899122] mmc0: host does not support reading read-only switch, assuming write-enable
[0.902102] mmc0: new high speed SDHC card at address 0007
[0.903429] mmcblk0: mmc0:0007 SD32G 29.1 GiB (quirks 0x80000000)
[0.905600] mmcblk0: p1 p2
[0.909092] random: fast init done
[0.911296] mmc1: queuing unknown CIS tuple 0x08 (64 bytes)
[0.919012] mmc1: new high speed SDIO card at address 0001
[0.946538] EXT4-fs (mmcblk0p2): mounted filesystem with ordered data mode. Opts: (null)
[0.946595] VFS: Mounted root (ext4 filesystem) readonly on device 179:2.
[0.955515] devtmpfs: mounted
[0.960851] Freeing unused kernel memory: 1024K
[0.961934] Indeed it is in host mode hprt0 = 00021501
[1.022319] Run /sbin/init as init process
[1.171853] usb 1-1: new high-speed USB device number 2 using dwc_otg
[1.172001] Indeed it is in host mode hprt0 = 00001101
[1.412167] usb 1-1: New USB device found, idVendor=0424, idProduct=2514, bcdDevice= b.b3
[1.412184] usb 1-1: New USB device strings: Mfr=0, Product=0, SerialNumber=0
[1.412887] hub 1-1:1.0: USB hub found
[1.412983] hub 1-1:1.0: 4 ports detected
[1.674838] systemd[1]: System time before build time, advancing clock.
[1.731841] usb 1-1.1: new high-speed USB device number 3 using dwc_otg
[1.834721] NET: Registered protocol family 10
[1.836005] Segment Routing with IPv6
[1.862212] usb 1-1.1: New USB device found, idVendor=0424, idProduct=2514, bcdDevice= b.b3
[1.862229] usb 1-1.1: New USB device strings: Mfr=0, Product=0, SerialNumber=0
[1.862844] hub 1-1.1:1.0: USB hub found
[1.862934] hub 1-1.1:1.0: 3 ports detected
[1.899842] systemd[1]: systemd 241 running in system mode. (+PAM +AUDIT +SELINUX +IMA +APPARMOR +SMACK +SYSVINIT +UTMP +LIBCRYPTSETUP +GCRYPT +GNUTLS +ACL +XZ +LZ4 +SECCOMP +BLKID +ELFUTILS +KMOD -IDN2 +IDN -PCRE2 default-hierarchy=hybrid)
[1.900736] systemd[1]: Detected architecture arm.
[1.908861] systemd[1]: Set hostname to <raspberrypi>.
[1.918113] systemd[1]: Failed to bump fs.file-max, ignoring: Invalid argument
[1.961914] usb 1-1.2: new low-speed USB device number 4 using dwc_otg
[2.118208] usb 1-1.2: New USB device found, idVendor=413c, idProduct=2113, bcdDevice= 1.08
[2.118227] usb 1-1.2: New USB device strings: Mfr=0, Product=2, SerialNumber=0
[2.118249] usb 1-1.2: Product: Dell KB216 Wired Keyboard
[2.135882] input: Dell KB216 Wired Keyboard as /devices/platform/soc/3f980000.usb/usb1/1-1/1-1.2/1-1.2:1.0/0003:413C:2113.0001/input/input0
[2.202472] hid-generic 0003:413C:2113.0001: input,hidraw0: USB HID v1.11 Keyboard [Dell KB216 Wired Keyboard] on usb-3f980000.usb-1.2/input0
[2.220448] input: Dell KB216 Wired Keyboard System Control as /devices/platform/soc/3f980000.usb/usb1/1-1/1-1.2/1-1.2:1.1/0003:413C:2113.0002/input/input1
[2.282187] input: Dell KB216 Wired Keyboard Consumer Control as /devices/platform/soc/3f980000.usb/usb1/1-1/1-1.2/1-1.2:1.1/0003:413C:2113.0002/input/input2

[2.282412] hid-generic 0003:413C:2113.0002: input,hidraw1: USB HID v1.11 Device [Dell KB216 Wired Keyboard] on usb-3f980000.usb-1.2/input1

[2.290020] systemd[1]: File /lib/systemd/system/systemd-journald.service:12 configures an IP firewall (IPAddressDeny=any), but the local system does not support BPF/cgroup based firewalling.

[2.290044] systemd[1]: Proceeding WITHOUT firewalling in effect! (This warning is only shown for the first loaded unit using IP firewalling.)

[2.381875] usb 1-1.3: new full-speed USB device number 5 using dwc_otg

[2.526632] usb 1-1.3: New USB device found, idVendor=413c, idProduct=301d, bcdDevice=0.09

[2.526647] usb 1-1.3: New USB device strings: Mfr=1, Product=2, SerialNumber=0

[2.526657] usb 1-1.3: Product: Dell Universal Receiver

[2.526666] usb 1-1.3: Manufacturer: Dell

[2.535169] input: Dell Dell Universal Receiver as /devices/platform/soc/3f980000.usb/usb1/1-1/1-1.3/1-1.3:1.0/0003:413C:301D.0003/input/input3

[2.602943] hid-generic 0003:413C:301D.0003: input,hidraw2: USB HID v1.11 Keyboard [Dell Dell Universal Receiver] on usb-3f980000.usb-1.3/input0

[2.612624] input: Dell Dell Universal Receiver Mouse as /devices/platform/soc/3f980000.usb/usb1/1-1/1-1.3/1-1.3:1.1/0003:413C:301D.0004/input/input4

[2.613128] input: Dell Dell Universal Receiver Consumer Control as /devices/platform/soc/3f980000.usb/usb1/1-1/1-1.3/1-1.3:1.1/0003:413C:301D.0004/input/input5

[2.682125] input: Dell Dell Universal Receiver System Control as /devices/platform/soc/3f980000.usb/usb1/1-1/1-1.3/1-1.3:1.1/0003:413C:301D.0004/input/input6

[2.682403] hid-generic 0003:413C:301D.0004: input,hidraw3: USB HID v1.11 Mouse [Dell Dell Universal Receiver] on usb-3f980000.usb-1.3/input1

[2.689002] hid-generic 0003:413C:301D.0005: hiddev96,hidraw4: USB HID v1.11 Device [Dell Dell Universal Receiver] on usb-3f980000.usb-1.3/input2

[2.795842] random: systemd: uninitialized urandom read (16 bytes read)

[2.807590] random: systemd: uninitialized urandom read (16 bytes read)

[2.811995] systemd[1]: Created slice User and Session Slice.

[2.812295] random: systemd: uninitialized urandom read (16 bytes read)

[2.814997] systemd[1]: Created slice system-getty.slice.

[2.815786] systemd[1]: Listening on Journal Socket (/dev/log).

[2.816447] systemd[1]: Listening on udev Control Socket.

[2.934361] usb 1-1.1.1: new high-speed USB device number 6 using dwc_otg

[3.043020] i2c /dev entries driver

[3.062440] usb 1-1.1.1: New USB device found, idVendor=0424, idProduct=7800, bcdDevice=3.00

[3.062456] usb 1-1.1.1: New USB device strings: Mfr=0, Product=0, SerialNumber=0

[3.337335] lan78xx 1-1.1.1:1.0 (unnamed net_device) (uninitialized): No External EEPROM. Setting MAC Speed

[3.338535] libphy: lan78xx-mdiobus: probed

[3.357705] lan78xx 1-1.1.1:1.0 (unnamed net_device) (uninitialized): int urb period 64

[3.649997] EXT4-fs (mmcblk0p2): re-mounted. Opts: (null)

[3.760493] systemd-journald[114]: Received request to flush runtime journal from PID 1

[4.682225] vc_sm_cma: module is from the staging directory, the quality is unknown, you have been warned.

[4.685222] media: Linux media interface: v0.10

[4.685382] bcm2835_vc_sm_cma_probe: Videocore shared memory driver

[4.685394] [vc_sm_connected_init]: start

[4.701038] [vc_sm_connected_init]: installed successfully

[4.776356] videodev: Linux video capture interface: v2.00

[4.872423] snd_bcm2835: module is from the staging directory, the quality is unknown, you have been warned.
[4.896374] bcm2835_mmal_vchiq: module is from the staging directory, the quality is unknown, you have been warned.
[4.912561] bcm2835_mmal_vchiq: module is from the staging directory, the quality is unknown, you have been warned.
[4.946646] bcm2835_codec: module is from the staging directory, the quality is unknown, you have been warned.
[4.947382] bcm2835_v4l2: module is from the staging directory, the quality is unknown, you have been warned.
[4.967423] bcm2835-codec bcm2835-codec: Device registered as /dev/video10
[4.967466] bcm2835-codec bcm2835-codec: Loaded V4L2 decode
[4.976575] bcm2835-codec bcm2835-codec: Device registered as /dev/video11
[4.976616] bcm2835-codec bcm2835-codec: Loaded V4L2 encode
[4.983433] bcm2835_audio soc:audio: card created with 8 channels
[4.984126] bcm2835-codec bcm2835-codec: Device registered as /dev/video12
[4.984164] bcm2835-codec bcm2835-codec: Loaded V4L2 isp
[7.152269] random: crng init done
[7.152281] random: 7 urandom warning(s) missed due to ratelimiting
[8.100346] uart-pl011 3f201000.serial: no DMA platform data
[8.133412] 8021q: 802.1Q VLAN Support v1.8
[8.422640] cfg80211: Loading compiled-in X.509 certificates for regulatory database
[8.574712] cfg80211: Loaded X.509 cert 'sforshee: 00b28ddf47aef9cea7'
[11.360216] IPv6: ADDRCONF(NETDEV_UP): eth0: link is not ready
[11.360234] 8021q: adding VLAN 0 to HW filter on device eth0
[12.406367] Adding 102396k swap on /var/swap. Priority:-2 extents:1 across:102396k SSFS
[15.269243] Bluetooth: Core ver 2.22
[15.269311] NET: Registered protocol family 31
[15.269315] Bluetooth: HCI device and connection manager initialized
[15.270193] Bluetooth: HCI socket layer initialized
[15.270209] Bluetooth: L2CAP socket layer initialized
[15.270249] Bluetooth: SCO socket layer initialized
[15.294270] Bluetooth: HCI UART driver ver 2.3
[15.294283] Bluetooth: HCI UART protocol H4 registered
[15.294378] Bluetooth: HCI UART protocol Three-wire (H5) registered
[15.296504] Bluetooth: HCI UART protocol Broadcom registered
[15.665427] Bluetooth: BNEP (Ethernet Emulation) ver 1.3
[15.665444] Bluetooth: BNEP filters: protocol multicast
[15.665462] Bluetooth: BNEP socket layer initialized
[15.732860] Bluetooth: RFCOMM TTY layer initialized
[15.732881] Bluetooth: RFCOMM socket layer initialized
[15.732898] Bluetooth: RFCOMM ver 1.11
[30.441060] fuse init (API version 7.27)